

Spur Protector (SPLB1/13)

Ideal for industrial or commercial applications. The 'Spur Protector' SPLB1/13 provides an economic means of preventing damage to sensitive electronic equipment on individual ring mains, from the dangers of transients, which can occur as the result of a nearby lightning strike or surges derived from the switching of inductive or capacitive loads.

The Spur Protector can either be wired to the equipment as an inline protector or can be hardwired into wall mounted conduits.

The Spur Protector is best used as part of a totally integrated surge protection system and should be considered as the 'final link in the chain' when planning a systematic and co-ordinated approach to surge protection and it is therefore essential that main service and distribution panel protection is provided as a 'first line' of defence.


The Spur Protector provides suppression from mainsborne voltage spikes and surges between live and earth, live and neutral and neutral and earth conductors, thus ensuring protection in all three modes. This protection is achieved by using high energy absorbing elements which are accurately matched to the internal fuse protection of the Spur Protector.

Two status lights are provided - red and green. The green neon indicates mains power 'ON'. The red neon when lit indicates loss of protection.

The Spur Protector features high surge current handling capability which under normal conditions will automatically reset after clamping smaller, more frequently occurring surges. However, should a large surge current, in excess of 6.5kA appear on the line it will be clamped by the Spur Protector, but protection will be lost.

In this instance, the red neon illuminates to indicate that protection is no longer present and the unit should be replaced. With both lights on, power will still be supplied to the load, but without surge protection.



	SPLB1/13
Specification	
Operating Voltage	230 Volts rms nominal 280 volts rms max
Maximum Current Rating	13 Amps
Leakage Current*	125µA at 230V rms
Maximum Surge Current Handling (8/20µs)	6.5kA
Response time	<10ns
Let Through Voltage at 3kA 8/20µs	850 volts L-N, L-E, N-E
Location Category BS6651: 1999 Annex C	B
Status indication	Green - Power 'ON' Protection Operational Green & Red - Power 'ON' No Protection
Case:	Steel - epoxy paint
Dimensions (in mm) L W D	142 80 44
Weight (in grams)	431
Order Code	SPLB1/13-BOW

*The surge protection devices commence clamping surges as low as 450 volts and therefore appear as less than 2 Mohms resistance at 500V DC.

All of the above information, including drawings, illustrations and graphic designs, reflects our present understanding and is to the best of our knowledge and belief correct and reliable. Users, however, should independently evaluate the suitability of each product for the desired application. Under no circumstances does this constitute an assurance of any particular quality or performance. Such an assurance is only provided in the context of our product specifications or explicit contractual arrangements. Our liability for these products is set forth in our standard terms and conditions of sale.

Contacts

PD Devices Ltd
 Old Station Yard,
 South Brent,
 Devon,
 TQ10 9AL
 United Kingdom.

Telephone : +44 01364 649248
 Facsimile : +44 01364 649250
 E-mail Enquiries : enquiries@pddevices.co.uk
 Web Site : www.pddevices.co.uk