


19" Rack Mount IEC C13 Surge & RFI Protected Trailing Leads



PD Devices BS1363 19" rack mount surge & RFI protected unit is an ideal solution for any 19" rack based equipment. The ruggedized powder coated steel cases ensure a high impact resistance and long working life.

Units have a 2U high enclosure and are supplied with a 2 meter lead and BS1363 plug. Surge protection exceeds the requirements of BS6651: 1999 Annex C, location category B.

Specification:

Voltage Rating (Nominal)	230V rms
Maximum Current Rating	10A
Power Consumption	Negligible
Lead Length	2m
Surge Handling (8/20us) [Per Element]	19.5kA [6.5kA]
Average Attenuation, Symmetric 1-30MHz (dB)	-50
Voltage Protection Level (Up) 8/20us	900V@3kA 8/20us
Response Time	<10ns
BS6651:1999 Annex C Location Category	A & B

Standard Features:

- Illuminated switch to show power on.
- Durable powder coated steel construction.
- 8 Sockets

PD Devices Ltd. Old Station Yard, South
 Brent, Devon. TQ10 9AL.
 T: +44 (0)1364 649248
 F: +44 (0)1364 649250
 E: contact@pddevices.co.uk

- Order Code:

8	3	8	IEC/GB
---	---	---	--------

If you cannot see the socket configuration or additional features that you need, please call our customer service department on +44 (0)1364 649248 to discuss your requirements.

PD Devices Ltd. Old Station Yard, South
Brent, Devon. TQ10 9AL.
T: +44 (0)1364 649248
F: +44 (0)1364 649250
E: contact@pddevices.co.uk